

Diamond Pro<sup>®</sup> RETAINING WALL SYSTEM



Architects, engineers and contractors are choosing the Diamond Pro® retaining wall system to create flexible, costeffective solutions for a broad range of large commercial, municipal and residential retaining wall projects. For contours that shape new environments and colors that blend with the surroundings, the natural choice is Diamond Pro blocks.

Aesthetically, the natural rock texture and earth-tone colors blend easily into any environment. Diamond Pro products can be used with geosynthetic reinforcement for tall-wall applications.

- One square foot of wall face per block
- Can be used to build gravity walls up to 4 feet high, including buried course, but excluding the cap\*
- Original rear-lip locator
- Taller walls can be built with geosynthetic reinforcement or the Anchorplex<sup>™</sup> retaining wall system when designed by a qualified engineer
- ICC evaluated

## Straight Face

• Minimum outside radius, measured on the top course to the front of the units: 4 feet

• Minimum inside radius, measured on the base course to the front of the units: 6 feet

## **Beveled Face**

- Minimum outside radius, measured on the top course to the front of the units: 2 feet
- Minimum inside radius, measured on the base course to the front of the units: 4 feet

\*This height assumes cores are filled with drainage aggregate, level backfill and clean, compacted sand or gravel and no surcharge.







\*Product dimensions are height by face length by depth. Actual dimensions and weights may vary from these approximate values due to variations in manufacturing processes. Specifications may change without notice. See your Anchor representative for details, color options, block dimensions and additional information.

© 2011 Anchor Wall Systems, Inc. The Diamond Pro\* wall system is manufactured under license from Anchor Wall Systems, Inc. (AWS). The "Anchor A" and "Anchor Build Something Beautiful" logos, "Anchorplex" and "Diamond Pro" are trademarks of AWS. The wall system blocks are covered by the AWS Limited Warranty. For a complete copy, visit your local dealer or see anchorwall.com.

Anchor Wall Systems, Inc., 5959 Baker Road, Suite 390, Minnetonka, MN 55345.

## See anchorwall.com for installation instructions.

and the second	Contraction of the second
Straight Face	Beveled Face
8" x 18" x 12"	8" × 18" × 12"
74 lbs.	72 lbs.
1.00 sq. ft.	1.00 sq. ft.
1″/7.1°	1″/7.1°
	8" x 18" x 12" 74 lbs. 1.00 sq. ft.





Accessory Units	Сар	Corner
Approximate Dimensions*	Front, 4" x 17¼" x 10³/8" Back, 4" x 12" x 10³/8"	8" × 18" × 9" 8" × 18" × 9"
Approximate Weight*	47 lbs.	101 lbs.
Coverage	1.22 lin. ft.	1.50 sq. ft.

A&B0810

73.3068.1 08/11 4015

